

1,4-Dioxane Remediation by XSVE

Project Team

ESTCP Funded



- IST
 - ◆ Rob Hinchee, PhD, PE – PI
 - ◆ Dave Burris, PhD, PG – Project Geochemist
- Colorado School of Mines
 - ◆ Paul Johnson, PhD – HypeVent Lead and Technical Advisor
- Arizona State University
 - ◆ Paul Dahlen, PhD – Technical Advisor and Lab Lead
- AECOM
 - ◆ Kimiye Touchi, PE & Paul Graff, PE – McClellan Remediation Team
- AFCEC
 - ◆ Ken Smarkel, PhD, PE – McClellan Program Manager
 - ◆ Hunter Anderson, PhD – Technical Advisor
- US Army Corps of Engineers
 - ◆ Dave Becker, PG – Technical Advisor

Technical Objectives

- Design, implement, and document successful remediation of 1,4-dioxane in the vadose zone.
 - *Adapt SVE to address 1,4-dioxane - enhanced or extreme SVE (XSVE).*
- Develop a tool to aid in XSVE system design and provide for effective technology transfer.
 - *Update the HypeVent SVE software package (original HypeVent helped promote the current widespread application of SVE).*
 - *Produce a succinct, common sense, effective guidance document incorporating HypeVent.*



Site Description

Former McClellan AFB, CA
OU D



VES-105 PneuLog Results


Concentrations and Effective Permeability Obtained during SVE Operation



**XSVE Screened Interval
38 to 68 ft bgs**


Test Design

- 4 injection wells - 20 ft corners
 - ~100 cfm; ~100 to 120 °C
- 1 extraction well – center
 - ~100 cfm
- low carbon steel well casing
- concrete grout
- screened interval 38 – 68 ft
- existing vapor treatment system
- condensate collection




Well & Sensor Locations

VMW Locations – Multi-Level Sensors/Probes




- Temperature (T)
- Soil Moisture (SM)
- Soil Gas Probes (SG)



Well Installations



XSVE System




Pre- and Post- Soil Borings

For 1,4-Dioxane & Soil Moisture


Cross-Section View

Plan View



- = initial soil borings
- = final soil borings

5 initial soil borings
5 final soil borings



Each Soil Boring:


1 soil composite above

10 soil composites in
treatment zone
(screened interval)

2 soil composites below


ITRC Incremental Sampling Method: Center; Inner Ring; Outer Ring

Cross-Section




Operation (Injection & Extraction Wells)

Injection




Extraction




Outer Ring

VMW-2




VMW-4




Inner Ring


VMW-1



VMW-3




Operation (1,4-Dioxane Mass Removal)





- Mass removal estimates (~13 kg 1,4-dioxane at shutdown) consistent with before and after soil concentrations
- Initial removal rate consistent with SVE well next to demonstration.

Performance Assessment (1,4-Dioxane Removal)




- 95% Loss Within Treatment Zone
- Decrease Below Treatment Zone

HypeVent Model (Paul Johnson, CSM)




Agrees with Field Results

1,4-Dioxane Henry's Constant



- Henry's Constant increases ~17-fold from 10 to 60°C.
- SVE removal efficiency for 1,4-dioxane should increase at elevated temperatures.

HypeVent Model (Sensitivity Analysis)



Heating Improved 1,4-Dioxane Removal Efficiency

Summary and Conclusions

- SVE can remediate 1,4-dioxane
 - *~95% mass removal in this study*
- However high flow rates are required
 - *~20,000 Void volumes in this study compared to*
 - *200 to 5,000 Void volumes for conventional SVE*
- Heating helps
 - *Estimated cost of heating ~\$25/yd in this study*
 - 100 to 120 C injection
 - *More heat would accelerate the process, but could increase costs*